

1

METHOD AND APPARATUS FOR SWITCHING OPTICAL
SIGNALS WITH A PHOTON BAND GAP DEVICE

TECHNICAL FIELD OF THE INVENTION

This invention relates in general to communication with optical signals and, more particularly, to a method and apparatus for effecting switching of optical signals.

BACKGROUND OF THE INVENTION

Telecommunications is a field which has been rapidly evolving over the past twenty years, fueled in part by the progressively increasing popularity of technologies such as cellular telephones, facsimile machines, and computer communications that use the Internet. Due to these growing new technologies, there has been a progressively increasing demand for telecommunications equipment with greater information-carrying capacity, which in turn has created a progressively increasing focus on effecting communications through the use of optical signals.

High bandwidth fiber optic telecommunication systems are being deployed around the world. This is creating a backbone system which couples major metropolitan areas. Currently, when these existing systems need to effect switching of an optical signal, they typically convert the optical signal into an electrical signal, effect electrical switching of the electrical signal, and then convert the resulting electrical signal back into an optical signal. This greatly delays the propagation of information through the system, and is expensive because it increases the complexity of the system.

In order to avoid this problem, attempts are being made to develop optical switches which would directly switch optical signals, without temporarily converting them into electrical signals. Technologies which are being considered include micro-electro-opto-mechanical switches, bubble jets, liquid crystal arrays, moving opto-mechanical mirrors or prisms, electro-optic controlled coupled waveguides, and thermally controlled coupled waveguides. While these existing approaches have

been generally satisfactory for their intended purposes,
they have not been satisfactory in all respects. To some
extent, these approaches involve problems such as poor
reliability, high insertion or transmission losses,
5 difficulty in scaling these switching approaches to
larger sizes, and costly manufacturing techniques.
Further, these existing approaches have relatively slow
switching speeds, on the order of approximately a few
milliseconds.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2

SUMMARY OF THE INVENTION

From the foregoing, it may be appreciated that a need has arisen for a method and apparatus for processing optical signals, which avoids at least some of the problems discussed above. According to the present invention, this need is addressed by the provision of a method and apparatus for operating an optical switch which includes an input for optical radiation, an output spaced from the input, and a first region disposed optically between the input and the output. The method and apparatus involve: providing within the first region a plurality of second regions and a third region, the second regions being provided at a spaced locations within the first region, and the third region having an index of refraction and being a portion of the first region other than the second regions; subdividing the second regions into first and second groups which are mutually exclusive, the second regions of the second group being arranged along a path which extends through the first region from the input to the output and which is free of the second regions of the first group; and selectively operating the switch in first and second operational modes, wherein in the first operational mode each of the second regions has an index of refraction different from the index of refraction of the third region so that the third region and the second regions cooperate to prevent optical radiation with a predetermined wavelength from propagating within the first region, and wherein in the second operational mode each of the second regions of the first group has an index of refraction different from the index of refraction of the third region so that the third region

and the second regions of the first group cooperate to prevent radiation with the predetermined wavelength from propagating within portions of the first region other than along the path, and in which each of the second regions of the second group has an index of refraction selected in relation to the index of refraction of the third region so as to permit radiation with the predetermined wavelength to propagate through the first region along the path from the input toward the output.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention will be realized from the detailed description which follows, taken in conjunction with the accompanying drawings, in which:

FIGURE 1 is a diagrammatic top view of an optical switch which embodies the present invention;

FIGURE 2 is a diagrammatic sectional side view of the optical switch of FIGURE 1, taken along the line 2-2 in FIGURE 1, and also diagrammatically shows a control circuit for the optical switch;

FIGURE 3 is a diagrammatic sectional top view taken along the line 3-3 in FIGURE 2, and shows a first operational mode of the optical switch;

FIGURE 4 is a diagrammatic sectional top view similar to FIGURE 3, but showing a second operational mode of the optical switch;

FIGURE 5 is a diagrammatic sectional top view similar to FIGURES 3-4, but showing a third operational mode of the optical switch;

FIGURE 6 is a diagrammatic sectional top view similar to FIGURES 3-5, but showing a fourth operational mode of the optical switch;

FIGURE 7 is a diagrammatic top view of an optical switch which is an alternative embodiment of the optical switch of FIGURE 1;

FIGURE 8 is a diagrammatic sectional side view of an optical switch which is still another alternative embodiment of the optical switch of FIGURE 1; and

FIGURE 9 is a diagrammatic sectional side view similar to FIGURE 8, but showing a different operational mode of the optical switch of FIGURE 8.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 is a diagrammatic top view of an optical switch 11 which is part of an apparatus 10 that embodies the present invention. FIGURE 2 is a diagrammatic sectional side view taken along the line 2-2 in FIGURE 1, showing the optical switch 11, and also showing diagrammatically in broken lines a control circuit 12 which is a further part of the apparatus 10.

The optical switch 11 has one input and three outputs. In particular, with reference to FIGURE 1, optical radiation can be supplied at 16 to an edge of the optical switch 11 which serves as an input, and this optical radiation can subsequently exit the optical switch 11 at any one of three locations that are disposed along another edge thereof, and that serve as respective optical outputs, as indicated diagrammatically by three arrows 17-19.

The embodiment of FIGURES 1-2 is configured for use with radiation having a wavelength of approximately 1.5 μm , which is a form of radiation commonly used for optical communication in the telecommunication industry. However, the present invention is suitable for use with radiation at a wide variety of other wavelengths. Further, the switch 11 of FIGURE 1 is described herein for convenience as having a single input for the radiation 16, and three outputs corresponding to the radiation at 17-19. However, it will be recognized that the outputs could be inputs and that the input could serve as output. In fact, communications through the optical switch 11 could be bi-directional.

With reference to FIGURE 2, the optical switch 11 includes a generally platelike member 26, which has

planar top and bottom surfaces that are parallel. The member 26 has an approximately rectangular shape in a top view, corresponding to the outline of the switch 11 as seen in FIGURE 1. The member 26 is made from fused silica glass, but could alternatively be made from single crystal silicon, chalcogenide glass, gallium arsenide, or some other suitable material. The material of the member 26 is inherently transmissive to radiation at the wavelength of interest, although there is other structure within the switch 11 which tends to control the extent to which radiation of interest is or is not permitted to propagate through the member 26, as discussed later.

A not-illustrated optical fiber carrying the input radiation 16 could be fused to the edge of the member 26 in a known manner, for example using the beam of a laser. Three additional optical fibers, which are also not illustrated, could be fused to respective locations along the edge of the member 26 in order to respectively receive the output radiation designated at 17-19.

The member 26 has a plurality of spaced cylindrical openings extending vertically through it, twelve of which are identified with reference numerals 31-42. The openings are arranged in a regular, periodic pattern, where the spacing 46 between adjacent openings in each row is the same as the spacing 47 between adjacent openings in each column. In the embodiments of FIGURES 1-2, the spacing at 46 and 47 is approximately 0.8 to 1.0 μm , and the openings each have a diameter of approximately 0.5 μm . The openings in each row have, with respect to openings in the adjacent rows, an offset 48 in the direction of the row. Similarly, the openings in each column have, with respect to the openings in

adjacent columns, an offset 49 in the direction of the columns. The offsets 48 and 49 are the same, and are each half the value of the spacing at 46 or 47.

5 The openings in the member 26 can be formed in any convenient manner. One suitable technique is to pattern the top surface of the member 26 using photolithography, holography, laser writing, or electron beam writing, so as to define a plurality of circular regions arranged in the periodic offset pattern which is shown in FIGURE 1.
10 An etching process would then be carried out on the top surface of the member 26, in order to etch a respective opening therethrough where each circular region has been patterned.

15 Seven electrodes 51-57 are provided on the top surface of the member 26. In the disclosed embodiment, the electrodes 51-57 are each made from indium tin oxide (ITO), but there are other suitable materials from which the electrodes could alternatively be made. The electrode 51 covers the openings 31-32, the electrode 52 covers the openings 33-34, the electrode 53 covers the openings 35-36, the electrode 54 covers the openings 37-38, the electrode 55 covers the openings 39-40, and the electrode 56 covers the openings 41-42. The remaining electrode 57 covers all of the other openings in the
20 member 26. Seven additional electrodes are provided on the bottom surface of the member 26, in a configuration which is a mirror image of the electrodes 51-57. Four of these additional electrodes are visible in FIGURE 2, and are identified by reference numerals 61-63 and 67.
25 Although the disclosed embodiment has seven separate electrodes on the bottom surface of the member 26, it would alternatively be possible to instead provide a
30

single common electrode over substantially the entire bottom surface of the member 26, such that respective electrical voltages applied to the seven electrodes 51-57 on the top surface are all referenced to the single bottom electrode.

Each of the openings in the member 26 is filled with a liquid crystal material of a known type, for example as indicated at 71 in FIGURE 2. The liquid crystal material is introduced into the openings before the electrodes are mounted on the member 26, for example by spinning or depositing the liquid crystal material onto the member 26. Although the disclosed embodiment uses a liquid crystal material, it would alternatively be possible to use some other electro-optically active material, such as chalcogenide glass, or other oxide crystals and polymers known to persons skilled in the art.

As is known in the art, a liquid crystal material will change its index of refraction, or dielectric constant, when an electric voltage is applied to it. The liquid crystal material 71 is transmissive to the radiation of interest. However, depending on its current index of refraction, the liquid crystal material and the material of member 26 may permit or prevent the propagation of radiation, as discussed in detail later.

The control circuit 12 is configured to be able to selectively apply a respective voltage between each pair of electrodes disposed on opposite sides of the member 26. For example, as shown diagrammatically by broken lines in FIGURE 2, the control circuit 12 can selectively apply a voltage between the electrode pair which includes the electrodes 51 and 61. Similarly, the control circuit 12 can selectively apply a voltage between the electrode

pair which includes the electrodes 52 and 62, a further voltage between the electrode pair which includes electrodes 53 and 63, and yet another voltage between the electrode pair which includes the electrodes 57 and 67. These voltages are used to control the state of the liquid crystal material within the openings through the member 26, which in turn has the effect of controlling the index of refraction of this liquid crystal material. In this regard, the optical switch 11 of FIGURES 1-2 has four distinct modes of operation, which are each discussed separately below.

More specifically, in a first operational mode, the voltages applied to the respective electrode pairs have values that cause the liquid crystal material in each of the openings to have an index of refraction which is different from the index of refraction of the material of the member 26, in a manner establishing photon band gaps throughout the switch 11. In this first operational mode, the periodic pattern of the openings in the member 26, in cooperation with the different indexes of refraction of the member 26 and the liquid crystal material, serve to create an optical configuration which is known as a photon band gap configuration. A photon band gap configuration is also sometimes referred to as a photonic crystal.

In this regard, FIGURE 3 is a diagrammatic sectional top view taken along the line 3-3 in FIGURE 2, and is representative of the first operational mode. The openings in the member 26 are all shown in solid lines, to indicate that the liquid crystal material in these openings has an index of refraction which is different from the index of refraction of the material of member

26, in a manner establishing a photon band gap configuration. Optical radiation which is supplied at 16 to the input of the switch 11 will not be able to enter the member 26, or will be confined to a relatively small area in the region of the input, for example as indicated diagrammatically by broken lines at 81. In the disclosed embodiment, this operational mode occurs when the voltage applied by the control circuit 12 across each of the electrode pairs is zero volts, although it will be recognized that the switch 11 could be configured so that this first operational mode is established by the application of some other voltage between each electrode pair.

In a second operational mode of the switch 11, and with reference to FIGURE 1, the control circuit 12 applies a positive voltage between the electrode pair which includes electrode 51 and also between the electrode pair which includes electrode 54 (FIGURE 1). With reference to FIGURE 1, this causes the liquid crystal material in the openings 31-32 and 37-38 to change to a state having a different index of refraction. In the disclosed embodiment, this index of refraction is the same as the index of refraction of the material 26, but it could be some other index of refraction. Consequently, the liquid crystal material in the openings 31-32 and 37-38 no longer cooperates with the material of the member 26 in a manner defining a photon band gap configuration in the region of openings 31-32 and 37-38. Thus, a path is established through the optical switch 11, where the openings 31-32 and 37-38 lie along this path.

In this regard, FIGURE 4 is a diagrammatic sectional top view similar to FIGURE 3, but showing this second operational mode. The openings 31-32 and 37-38 are shown in broken lines in FIGURE 4, rather than in solid lines, in order to diagrammatically indicate that the portions of liquid crystal material in these openings now have the same index of refraction as the member 26, and thus appear to radiation to a part of the member 26. The above-mentioned path through the optical switch 11 is designated by a pair of L-shaped broken lines 86-87, the path being the region between these two broken lines. Optical radiation supplied at 16 to the input of the switch 11 will travel along this path, and will exit through the first output of the switch 11, as indicated by arrow 17. Although the radiation must effectively turn a right-angle corner in the region of opening 32, the nature of the photon band gap configuration disposed outside the path 86-87 forces the radiation to efficiently turn this corner with no perceptible loss. In fact, the path could be configured to include a corner which is more than 90° , and the radiation would efficiently turn this corner with no perceptible loss, due to the nature of the surrounding photon band gap configuration. Thus, the switch 11 is virtually lossless.

As discussed above, when an appropriate activating voltage is applied to the liquid crystal material in the disclosed embodiment, it changes to an index of refraction which is the same as the index of refraction of the material of member 26. However, it would be possible for the liquid crystal material to respond to an activating voltage by changing to an index of refraction

which is different from the index of refraction of the material of member 26, so long as these two different indexes of refraction permit the propagation of radiation along the path, rather than creating a photon band gap configuration within the path.

In a third operational mode of the switch 11, and with reference to FIGURE 1, a voltage of zero volts is applied to each electrode pair which includes one of the electrodes 53, 54, 56 and 57. A positive actuating voltage is applied to each of the electrode pairs which include one of the electrodes 51, 52 and 55. As a result, the liquid crystal material in each of the openings 31-34 and 39-40 assumes a state in which its index of refraction is the same as the index of refraction of the material of member 26.

FIGURE 5 is a diagrammatic sectional top view similar to FIGURES 3 and 4, but showing this third operational mode. A path from the input to the second output is indicated diagrammatically by two L-shaped broken lines 91 and 92, where the path lies between these lines, and where the openings 31-34 and 39-40 all lie along this path. Optical radiation supplied at 16 to the input of the switch 11 will travel along this path and exit the switch 11 at the second output, as indicated by arrow 18.

In a fourth operational mode of the switch 11, and with reference to FIGURE 1, the control circuit 12 supplies a potential of zero volts to each of the electrode pairs which includes one of the electrodes 54, 55 and 57. A positive activating voltage is applied to each electrode pair which includes one of electrodes 51, 52, 53, and 56. This causes the liquid crystal material

in each of the openings 31-36 and 41-42 to change to a state in which it has the same index of refraction as the material of member 26. FIGURE 6 is a diagrammatic sectional top view similar to FIGURES 3-5, but showing this fourth operational mode. FIGURE 6 includes two L-shaped broken lines 96 and 97, which delimit a path extending from the input to the third output, where the openings 31-36 and 41-42 all lie along this path. Optical radiation supplied at 16 to the input travels along this path, and exits the optical switch 11 at its third output, as indicated by arrow 19.

With reference to FIGURES 1-2, the openings in the member 26 which are associated with the pair of electrodes 51 and 61 have been described herein as containing a liquid crystal material, which is controlled by a voltage applied between the pair of electrodes 51 and 61. However, as evident from the foregoing discussion, the liquid crystal material in these openings has the same state and index of refraction in each of the four operational modes of the switch 11. Thus, it would be possible to omit the electrodes 51 and 61, and replace the liquid crystal material in the associated openings with a material which is not electrically controlled, and which has the non-varying index of refraction that is needed in these openings.

FIGURE 7 is a diagrammatic top view similar to FIGURE 1, but showing an optical switch 111 which is an alternative embodiment of the switch 11 of FIGURE 1. Equivalent parts are designated with the same reference numerals. The primary difference is that the electrode configuration used for the switch 11 has been replaced with a different electrode configuration. In particular,

a plurality of small circular electrodes are provided on the top surface of the member 26, four of these electrodes being identified by reference numerals 121-124. Each of the circular electrodes is associated with only one of the openings through the member 26. A plurality of further circular electrodes are provided in a similar manner on the bottom of the member 26. In the optical switch 111, the associated control circuit (which is not shown in FIGURE 7) can control the liquid crystal material in each opening independently from the liquid crystal material in all other openings. Therefore, the control circuit has a wide degree of flexibility to route radiation through the switch 111 in any one of many different ways. The switch 111 thus permits a $1 \times N$ switch to be implemented in a relatively compact size for any practical value of N.

FIGURE 8 is a diagrammatic sectional side view corresponding generally to FIGURE 2, but showing an optical switch 211 which is an alternative embodiment of the optical switch 11 of FIGURES 1-2. The primary difference is that, in FIGURE 8, changes to the refraction index of the material in the openings of the member 26 is effected mechanically or hydraulically, rather than by electrically controlling liquid crystals.

More specifically, the member 26 has an opening 213, which is one of the openings for which the index of refraction can be the same in all operational modes. Accordingly, this opening is filled with a solid material 214, which has an appropriate index of refraction different from the index of refraction of the member 26, so that these indexes of refraction cooperate to provide

a photon band gap configuration in the region of the opening 213.

A housing 216 is mounted on the top of the member 26, and contains an air chamber 217 which is in fluid communication with each of the openings in the member 26 for which different indexes of refraction are used for different modes, including the openings 31-36. Three housings 231-233 are mounted on an underside of the member 26, and each have a respective chamber 236-238 therein. A respective piston 241-243 is movably supported in each of the housings 231-233, so to vary the size of the associated chamber 236-238 therein. The pistons 241-243 can be moved independently of each other by any suitable control mechanism. The openings 31 and 32 communicate with the chamber 236 through respective fluid passageways, one of which is indicated at 246. Similarly, the openings 33 and 34 communicate with the chamber 237 through respective fluid passageways, and the openings 35 and 36 communicate with the chamber 238 through respective fluid passageways. The chambers 236-238 each contain a quantity of a fluid 251-253, which is selected for its index of refraction.

As mentioned above, the pistons 241-243 can all be controlled independently. However, for purposes of convenience, they are all shown in a raised position in FIGURE 8, in which the sizes of the chambers 236-238 have been effectively reduced in a manner which forces fluid up through the passageways and into the openings 31-36, while the air which was within these openings is forced up into the housing 216. The fluid moved into these openings has an index of refraction which is the same as the index of refraction of the material 26, so as to

avoid a photon band gap configuration in the region of each of the openings 31-36. Consequently, radiation propagates through the member 26 along a path associated with these openings.

5 FIGURE 9 shows a different operational mode of the switch 211, in which each of the pistons 241-243 has been moved downwardly, in order to enlarge the effective size of each of the chambers 236-238, which in turn causes the fluid to flow out of the openings 31-36, and to be
10 replaced by air from the air chamber 217 in housing 216. This air has an index of refraction which is different from the index of refraction of the member 26, thereby creating a photon band gap configuration in the region of each of the openings 31-36, which prevents the
15 propagation of radiation of interest in the region of these openings.

 The present invention provides a number of technical advantages. Once such technical advantage is the capability to effect switching of an optical signal
20 without converting the optical signal into an electrical signal, thereafter effecting the necessary switching using the electrical signal, and then converting the switched electrical signal back into an optical signal. As a result, optical switching can be effected rapidly
25 and cheaply, and at very high data rates. A single stream of optical data can be efficiently divided up in real time, with respective segments being routed to different destinations.

 Still another advantage is that the optical switch
30 according to the invention has no significant insertion or transmission loss. It can be easily and cheaply manufactured in volume, has a high reliability, and can

be easily scaled to fit various different applications. With respect to the embodiment in which the material in the opening is actually changed, an advantage is that the degree of change in the index of refraction can be greater than would be the case where the index of refraction of a single material is varied, for example under electrical control.

Although several selected embodiments have been illustrated and described in detail, it should be understood that various substitutions and alterations can be made therein without departing from the spirit and scope and of the present invention, as defined by the following claims.